

# DATA SHEET

## TESIRA® HARDWARE DIALER 1 (HD-1)



The Tesira HD-1 is a dialer for Tesira server-class devices. Housed in a stylish piece of hardware, this control interface provides access to all of the dialing functions of Tesira, with the look and feel of a traditional telephone dial pad. The Tesira HD-1 makes installations less expensive, easier to commission, and less complicated to operate. The HD-1 is compatible with Tesira SERVER and SERVER-IO with STC-2 or SVC-2 cards installed, as well as TesiraFORTÉ TI, TesiraFORTÉ VI, TesiraFORTÉ AVB TI, and TesiraFORTÉ AVB VI devices.

### BENEFITS

- Simple, intuitive design
- One-cable installation
- Configurable via Tesira software
- Access to all Tesira telephony functions
- Maintains the look and feel of a traditional enterprise phone

### FEATURES

- Telephony control over Ethernet
- Power over Ethernet (PoE)
- LCD display
- 12-button dial pad
- Four navigation buttons
- 100 programmable speed dial numbers
- Redial, call volume adjustment, mute, hold, and numerous other telephony functions
- Covered by Biamp Systems' five-year warranty

## ARCHITECTS & ENGINEERS SPECIFICATION

The hardware dialer shall be designed exclusively for use with Tesira® server-class devices. The dialer shall provide call initiation and termination functions for Biamp Tesira products. The dialer shall be PoE powered. The dialer shall use a single network interface for all communication, configuration, and control via a standard RJ-45 connector. The dialer shall have an LCD display screen. The dialer shall have a 12-key dial pad and shall include support for call volume adjustment, call mute, call bridging, on and off hook, hold, and redial last number. The dialer shall support 100 programmable speed dial numbers and feature scroll up/down, phone line 1 and phone line 2 buttons, flash, and 4 navigation buttons. The dialer shall be compliant with the RoHS directive. Warranty shall be five years. The hardware dialer shall be the Tesira HD-1.

## TESIRA HD-1 SPECIFICATIONS

<b>Network Connection:</b>	RJ-45 with Ethernet cable (CAT5, CAT5e, CAT6, or CAT7)	<b>Display:</b>	2.7 inch (69 mm) LCD
<b>Data/Control Cable Length:</b>	Up to 330ft (100m)	<b>Buttons:</b>	29 total - 12-key standard dial pad, 4 navigation buttons, 13 dedicated buttons
<b>Power:</b>	802.3af (PoE) Class 1	<b>Environmental:</b>	
<b>Control Programming:</b>	Tesira Design Software	Ambient Operating Temperature:	32 - 104 degrees F (0-40° C)
<b>Overall Dimensions:</b>		Humidity:	0-95% relative humidity (non-condensing)
Height:	1.57 inches (40 mm)	Altitude:	0-10,000 ft. (0-3000m) MSL
Width:	5.7 inches (145 mm)	<b>Compliance:</b>	UL and C-UL (USA and Canada)
Depth:	5.7 inches (145 mm)		FCC Part 15B (USA)
Weight:	0.9 lbs. (0.4 kg)		CE Marked* (Europe)
<b>Compatible with:</b>	Tesira SERVER and SERVER-IO with STC-2 or SVC-2 cards installed		RCM (Australia)
	TesiraFORTÉ TI		EAC (Eurasian Customs Union)
	TesiraFORTÉ VI		RoHS Directive (Europe)
	TesiraFORTÉ AVB TI		KCC (Korea)
	TesiraFORTÉ AVB VI		

\*Requires PoE insertion device to be CE marked